



Dimensions in mm

- Cavity Telecommunications Filter
- F_0 782 MHz, BW +/- 6 MHz
- Pass Band 776 to 788 MHz
- N-Type Connectors (m/f)
- Input Power 5W
- Wide Temperature Range -20°C to +60°C
- Low Insertion Loss

Specifications

Parameter	Unit	Minimum	Typical	Maximum
Center Frequency (F_0)	MHz	-	782	-
Pass Band	MHz	776		788
Band Width	MHz		$F_0 \pm 6$	
Impedance	Ohm		50	
Insertion Loss @ BW	dBa			1.0
Ripple	dB			0.5
Return Loss @ BW	dB	18		
VSWR				1.29:1
Attenuation @ 500 to 757 MHz @ 815 to 1000 MHz	dBc	45 48		
Input Power	Watt			5
Dimensions L x W x H (body without connectors)	mm inch		74 x 50 x 52 2.9 x 2.0 x 2.1	
Weight	kg lb		1.5 3.3	
Operating Temperature	°C	-20		+60

This product complies with EU directive 2002/95/EC (RoHS compliance)

Finish: black epoxy

Order Information

Type	Description
CAVBPF782H12-N	Band Pass Filter Cavity, 782 MHz, BW 12 MHz, N-Type Connectors (m/f)

Specifications subject to change without further notification

RF & Microwave Technology

AWT-Global provides advanced telecommunication technology products and analyzers for a variety of RF and Microwave applications.

High Performance Filters

Filters are paramount at any RF system. Our state of the industry cavity filters are satisfying most demanding requirements. Contact us for other frequency and attenuation requirements.

AWT Global

117 Grand Avenue
Hackettstown
New Jersey 07840, USA
p: +1 (973) 321-3423
e: sales@awt-global.com
w: www.awt-global.com

Frequency Response

