



- Economy Low PIM Load
- Power rating: 40 W
- Frequency: 698 MHz to 2700 MHz
- Dual connectors:
DIN 7/16 (m) & DIN 7/16 (f)
- Ear for lanyard or carbine
- Rubber protectors

Our economy low PIM load EPLOAD40 has been designed for field applications with budget oriented customers in mind. It offers good PIM rating and comes with two connectors, DIN 7/16 (m) and DIN 7/16 (f). This feature allows for conveniently connecting and testing devices with different connector genders. EPLOAD40 low PIM loads are rated for 40W of RF power (max 10 mins).

Specifications

Parameter	
Power rating	40 W: 10 min / 10 W : continuously
Frequency	698 to 2700 MHz
PIM rating	< -160 dBc (@ 2x43dBm)
Impedance	50 Ohms
Return Loss (RL)	20dB
Country of origin	USA

Order Information

Type	Description
EPLOAD40D	Economy Low PIM load 40W, 698 to 2700 MHz, DIN 7/16 (m/f) connectors

RF & Microwave Technology

AWT-Global provides advanced telecommunication technology products and analyzers for a variety of RF and Microwave applications.

AWT Global LLC

46 Countryside Apts.
Bldg. 6, Ste. 46
Hackettstown
New Jersey 07840, USA
p: +1 (973) 321-3423
e: sales@awt-global.com
w: www.awt-global.com

Specifications subject to change without further notification